

# WS1006E-2G4T-S

## 4-port 10/100/1000BASE-TX+2-port 1000Base-FX Industrial Ethernet Switch



WS1006E-2G4T-S is a hardened 6-port Industrial Ethernet Switch, providing non-blocking wire-speed performance in harsh industrial environments. It also provides 4-port 10/100/1000BASE-TX RJ45 + 2-port 1000Base-Fx delivered in an IP40 rugged, strong case with a redundant power system. Its slim case is suitable for such applications as surveillance system deployments, control management and wireless service in climatically demanding environments with a wide temperature range from -40°C to 75°C.

The WS1006E-2G4T-S series provides the flexibility to all kinds of 10/100Mbps Ethernet Media on RJ-45 port and performs highly stable fiber performance.

The WS1006E-2G4T-S series is packaged in a compact IP40 case with Din Rail Installation. It provides an integrated power supply with a wide range of voltages for worldwide operation. It also offers dual-redundant, reversible polarity 12V DC to 52V DC power supply inputs for high availability applications requiring dual or backup power inputs.

### Interface

- 4-port 10/100/1000Base-Tx RJ-45 with auto negotiation and auto-MDI/MDI-X function, supplying 30W PoE, compatible with 802.3AT/AF
- 2-port 1000Base-Fx interface SC/FC/ST/SFP
- Multi-Mode up to 2km
- Single-Mode up to 20km/40km/60km/80km

### Industrial conformance

- 48V to 57V DC, redundant power input
- -40°C to 75°C operating temperature
- IP40 steel alloy
- DIN-rail design

**Specifications:**

Model No.	<b>WS1006E-2G4T-SC2-S / WS1006E-2G4T-SC20-S / WS1006E-2G4T-S</b>
10/100/1000Base-TX Port	4 port RJ-45 auto-MDI / MDI-X
1000Base-FX Port	WS1006E-2G4T-SC2-S: 2 SC interface WS1006E-2G4T-SC20-S: 2 SC Interface WS1006E-2G4T-S: 2 SFP Slot
Fiber Port Type	WS1006E-2G4T-SC2-S: SC / multi-mode ,up to distance 2km ; WS1006E-2G4T-SC20-S: SC / single-mode ,up to distance 20km ; WS1006E-2G4T-S: Vary on module
Optical Frequency	WS1006E-2G4T-SC2-S: 1310nm WS1006E-2G4T-SC20-S: 1310nm WS1006E-2G4T-S: Vary on module
Performance Specification	Bandwidth: 20Gbps Packet Buffer Memory:2Mbit Packet Forwarding Rate:15Mpps MAC Address Table: 8K
Installation	DIN rail
Flow Control	Back pressure for half duplex, IEEE 802.3x pause frame for full duplex
Enclosure	Steel alloy
LED Indicator	Power: Red Fiber: Link 2(Green) Ethernet: Yellow
Power Input	12 to 52V DC redundant power
Power Consumption	< 10 watts
Network Protocols	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u;100Base-TX/FX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X;

	IEEE802.3x;
Network cables	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100meter) 1000BASE-TX: Cat6 or later UTP(≤100 meter)
Industry Standard	FCC CFR47 Part 15,EN55022/CISPR22, Class A IEC61000-4-2 (ESD): ±6kV (contact), ±8kV (air) IEC61000-4-3 (RS): 10V/m (80~1000MHz) IEC61000-4-4 (EFT): Power Port: ±2kV; Data Port: ±1kV IEC61000-4-5 (Surge): Power Port: ±1kV/DM, ±2kV/CM; Data Port: ±1kV IEC61000-4-6 (CS): 3V (10kHz-150kHz); 10V (150kHz-80MHz) IEC61000-4-16 (Common mode conduction): 30V (cont.), 300V (1s)
Certification	CE FCC Rohs compliance
Dimensions (W x D x H)	143.7 x 103 x 44.2 mm
Weight	Product Weight: 0.36KG Packing Weight: 0.46KG
Working Environment	Working temperature: -40~75℃ ; Storage temperature: -40~75℃ Relative Humidity: 5%~95 % ( no condensation)

## Ordering Information

<b>WS1006E-2G4T-S</b>	4-Port RJ45+2Port SFP (Interface optional ) , Industrial Switch, 1000Mbps
<b>WS1006E-2G4T-SC2-S</b>	4-Port RJ45+2Port SC (Interface optional ) , multi-mode ,up to distance 2km, Industrial Switch, 1000Mbps
<b>WS1006E-2G4T-ST2-S</b>	4-Port RJ45+2Port ST (Interface optional ) , multi-mode ,up to distance 2km, Industrial Switch, 1000Mbps
<b>WS1006E-2G4T-FC2-S</b>	4-Port RJ45+2Port FC (Interface optional ) , multi-mode ,up to distance 2km, Industrial Switch, 1000Mbps
<b>WS1006E-2G4T-SC20-S</b>	4-Port RJ45+2Port SC (Interface optional ) , single-mode ,up to distance 20km, Industrial Switch, 1000Mbps
<b>WS1006E-2G4T-ST20-S</b>	4-Port RJ45+2Port ST (Interface optional ) , single-mode ,up to distance 20km, Industrial Switch, 1000Mbps
<b>WS1006E-2G4T-FC20-S</b>	4-Port RJ45+2Port FC (Interface optional ) , single-mode ,up to distance 20km, Industrial Switch, 1000Mbps



-Industrial IoT product and digital solution provider-

Xiamen WideIoT Technology Co., Ltd



Website



[www.wideiot.com](http://www.wideiot.com)



+86-592-2031080



[info@wideiot.com](mailto:info@wideiot.com)



Xiamen softpark III .Fujian.China