

# WS2012E-4G8T-S

## 8-port 10//100/1000BASE-TX+4G SFP Managed Industrial Switch



**WS2012E-4G8T-S** is a hardened 10-port Industrial Ethernet Switch, providing non-blocking wire-speed performance in harsh industrial environments. It also provides 8-port 10/100/1000BASE-TX RJ45 +4G SFP delivered in an IP40 rugged, strong case with a redundant power system. Its slim case is suitable for such applications as surveillance system deployments, control management and wireless service in climatically demanding environments with a wide temperature range from -40°C to 75°C.

The **WS2012E-4G8T-S** provides the flexibility to all kinds of 10/100/1000Mbps Ethernet Media on RJ-45 ports and performs highly stable fiber performance.

The **WS2012E-4G8T-S** is packaged in a compact IP40 case with DIN rail installation. It offers dual-redundant, reversible polarity 12V DC to 52V DC power supply inputs for high availability applications requiring dual or backup power inputs.

### Interface

- 8-port 10/100/1000Base-Tx RJ-45 with auto negotiation and auto-MDI/MDI-X function
- 4-port gigabit SFP uplink

### Industrial conformance

- 12V to 52V DC, redundant power input
- -40°C to 75°C operating temperature
- IP40 Steel alloy housing
- DIN-rail hardware design

**Specifications:**

R040

Model No.	<b>WS2012E-4G8T-S</b>
1000Base-TX Port	8 port RJ-45 auto-MDI / MDI-X
1000Base-FX Port	4G SFP Slot
Performance Specification	Bandwidth: 56Gbps Packet Buffer Memory: 12Mbit Packet Forwarding Rate: 41.6Mpps MAC Address Table: 8K
Installation	DIN rail
Flow Control	Back pressure for half duplex, IEEE 802.3x pause frame for full duplex
Enclosure	IP40 slim type metal case
LED Indicator	Power: Red RUN: Green Fiber: Green Ethernet: Green
Power Input	12 to 52V DC redundant power
Power Consumption	< 10 watts
Network Protocols	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u;100Base-TX/FX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X; IEEE802.3x;
Network cables	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-TX: Cat6 or later UTP(≤100 meter)

Industry Standard	<p>FCC CFR47 Part 15,EN55032, Class A</p> <p>IEC61000-4-2 (ESD): ±6kV (contact), ±8kV (air)</p> <p>IEC61000-4-3 (RS): 10V/m (80~1000MHz)</p> <p>IEC61000-4-4 (EFT): Power Port: ±2kV; Data Port: ±1kV</p> <p>IEC61000-4-5 (Surge): Power Port: ±1kV/DM, ±2kV/CM; Data Port: ±1kV</p> <p>IEC61000-4-6 (CS): 3V (10kHz-150kHz); 10V (150kHz-80MHz)</p> <p>IEC61000-4-16 (Common mode conduction): 30V (cont.), 300V (1s)</p>
Dimensions (W x D x H)	143.7x124.8x42.5mm
Weight	<p>Product Weight: 1KG</p> <p>Packing Weight: 1.1KG</p>
Working Environment	<p>Working temperature: -40~75℃ ;</p> <p>Storage temperature: -40~85℃</p> <p>Relative Humidity: 5%~95 % ( no condensation)</p>

## Software:

Port Features	IEEE 802.3x Flow control
	Interface counters
	Storm Control
Link Aggregation	Static Aggregation
	Dynamic Aggregation, LACP
	Supports up to 8 aggregation groups, each group up to 8 ports Support source MAC, destination MAC, source destination MAC, source IP, destination IP, source destination IP routing strategy
Forwarding mode	Support IVL forwarding mode
Static MAC Address	Support
MAC Address Binding	Support
Mirror	Port-based Mirror
Spanning Tree	IEEE802.1d STP
	IEEE802.1w RSTP
	IEEE802.1s MSTP
ERPS (G.8032)	Single Ring, Sub-Ring, Multi-Ring
	Load balance

	Recovery Time < 50ms
GVRP	Supported
LLDP	LLDP
	LLDP-MED
Loop Protection	Supported
VLAN	4094 VLAN
	Port-based VLAN
	GVRP
Protocol VLAN	MAC-based VLAN
	IP Subnet-based VLAN
Voice VLAN	Static entry
Port Isolate	Support
IGMP	Snooping IGMP V1 Snooping
	IGMP V2 Snooping
	IGMP V3 Snooping
	IGMP Fast Leave
	IGMP Filter
MLD Snooping	MLD V1 Snooping
	MLD V2 Snooping
	MLD Fast Leave
	MLD Filter
<b>Security</b>	
ACL	ACL (IP Standard ACL), IPv4
	MAC extend ACL
	IP extend ACL
	L2, L3, L4 fields match
QoS	QoS Class, Remarking
	SP, WRR queue scheduling
	Ingress port-based rate-limit
	Ingress priority-based rate-limit
	Policy-based QoS
	Storm Control
	8 queues per port
Dot1x	Port Access Control
	Support 802.1x
	Support RADIUS
<b>Management</b>	

User management	Password protection
SNMP	SNMP V1/V2c/V3
RMON	Statistics Group
	Alarm Group
	Events Group
Web management	HTTP V1.1, HTTPS
Firmware Upgrade	Reversion Upgrade
IPv4/IPv6	Support
CLI	Support
Syslog/Debug	Support
Diagnosis	Ping (IPv4), ping (IPv6)
	Trace route(IPv4)
	Trace route(IPv6)
<b>Management</b>	
NTP	NTP Client
DHCP	DHCPv4 Client
DHCP Snooping	DHCP snooping table
	Trust Port
Telnet	Telnet Server
TFTP	TFTP Client
SSH	SSH Server

## Ordering Information

**WS2012E-4G8T-S**

8-port 10/100/100BASE-TX+4G SFP Managed Industrial Switch, IP40 Steel alloy housing



*-Industrial IoT product and digital solution provider-*



Website

*Xiamen WidelIoT Technology Co., Ltd*



*www.wideiot.com*



*+86-592-2031080*



*info@wideiot.com*



*Xiamen softpark III .Fujian.China*